

# Safety Data Sheet

## SECTION 1 : Identification

**A. GHS Product Name:** Anhydrous Industrial Ethanol

**B. Other means of identification :** Not available

**C. Recommended use of the chemical and restrictions on use**

**Recommended use :** Adhesives, sealants, Anti-Freeze and de-icing products, Washing and cleaning products, Metal surface treatment products (Electroplating agents), (Flame retardants and Fire preventing agents), Fuels and additives, Feed materials, Intermediates, Laboratory chemicals, Solvent and extraction agents, Stabilizers, Viscosity adjusters, Cosmetics, personal care products, Perfumes, fragrances, Pharmaceuticals, Fertilizers, Air care products, Biocidal products, Others

**Restriction on use :** Use for recommended use only

**D. Supplier's information**

**Company name :** Korea Alcohol Industrial Co., LTD.

**Address :** (Headquater) 14, Tapsil-ro 35beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do  
(Ulsan office) 66, Sanggae-ro, Nam-gu, Ulsan

**Telephone number :** (Headquater)031-881-8100, (Ulsan office)052-259-4761~2

**Respondent :** Not available

**Fax :** Not available

**E. Emergency phone number**

**Opening hours :** (Headquater)031-881-8100, (Ulsan office)052-259-4761~2

**Other comments (e.g. language(s) of the phone service) :** www.ka.co.kr / Sales or HSE Department

## SECTION 2 : Hazard identification

**A. Classification of the substance or mixture**

Flammable liquids : Category 2

Serious eye damage /eye irritation: Category 2

**B. GHS label elements, including precautionary statements**

**Pictogram and symbol :**



**Signal word :** Danger

**Hazard statements :**

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

**Precautionary statements**

**Prevention :**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection

**Response :**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use adequate to extinguish.

**Storage :**

P403+P235 Store in a well-ventilated place. Keep cool.

**Disposal :**

P501 Dispose of contents/container to in accordance with federal, state and local environmental control regulations.

**C. Other hazards which do not result in classification**

Not available

---

**SECTION 3: Composition/information on ingredients**

---

Chemical Name	Common Name (Synonyms)	CAS No.	EC number	Content (%)
Ethyl alcohol	Ethanol	64-17-5	200-578-6	99.9≤
Water	Water	7732-18-5*	231-791-2	<0.1
Acetaldehyde	Ethanal	75-07-0*	200-836-8	<0.1

Methyl alcohol	Methanol	67-56-1*	200-659-6	<0.1
<b>Isopropyl alcohol</b>	<b>2-Propanol</b>	<b>67-63-0*</b>	<b>200-661-7</b>	<b>&lt;0.1</b>
<b>n-Propyl alcohol</b>	<b>1-Propanol</b>	<b>71-23-8*</b>	<b>200-746-9</b>	<b>&lt;0.1</b>
<b>1,1-Ethyl Acetal</b>	<b>1,1-Diethoxyethane</b>	<b>105-57-7*</b>	<b>203-310-6</b>	<b>&lt;0.1</b>
Denatonium benzoate(Bitrex)	N-[2-(2,6-Dimethylphenyl)amino]-2-oxoethyl]-N,N-diethylbenzenemethanaminium benzoate	3734-33-6	223-095-2	<0.1

---

## SECTION 4: First-aid measures

---

### A. Description of necessary first-aid measures

- After eye contact** IF IN EYES: Rinse cautiously with water for several minutes. If possible, remove contact lenses. Keep washing  
If eye irritation persists: Get medical advice/attention.
- After skin contact** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
Call emergency medical service.  
Remove and isolate contaminated clothing and shoes.  
For minor skin contact, avoid spreading material on unaffected skin.  
In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.  
Wash skin with soap and water.
- After inhalation** IF exposed or concerned: Get medical advice/attention.  
Move victim to fresh air.  
Keep victim warm and quiet.
- After ingestion** IF exposed or concerned: Get medical advice/attention.

### B. Most important symptoms and effects, both acute and delayed

- Causes serious eye irritation

### C. Indication of immediate medical attention and notes for physician, if necessary

- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

---

## SECTION 5: Fire-fighting measures

---

### A. Suitable extinguishing media

- Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
- Use dry sand or earth to smother fire.

#### **B. Specific hazards arising from the chemical**

- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- Spilled material may cause fire or explosion hazard
- May cause vapor explosion and poison hazard indoors, outdoors or in sewers.
- Some of these materials may burn, but none ignite readily.
- Vapors may form explosive mixtures with air.
- May violently polymerize and result in fire and explosion.
- Vapors may travel to a source of ignition and ignite.
- Material may produce irritating and highly toxic gases by pyrolysis and combustion during burning
- May form explosive mixtures at the flashpoint or above.
- Highly flammable liquid and vapour

#### **C. Special protective actions for fire-fighters**

- Rescuers should put on appropriate protective gear.
- Evacuate area and fight fire from a safe distance.
- Many liquids are lighter than water.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas
- Substance may be transported hot.
- Substance may be transported in a molten form.
- Dike fire-control water for later disposal; do not scatter the material.
- Move containers from fire area if you can do it without risk.
- In case of the tank fire, extinguish at maximum distance or use unmanned fire extinguishing equipment.
- In case of the tank fire, keep cooling down the tank with plenty of water after fire is extinguished.
- In case of tank fire, if there is a high sound level on the pressure relief device or if the tank is discolored, immediately withdraw it.
- In the case of a tank fire, withdraw from the tank engulfed in flames.
- In the case of a large-scale fire of a tank, use unmanned fire extinguishing equipment and, if not possible, leave it to burn.

---

## **SECTION 6: Accidental release measures**

---

#### **A. Personal precautions, protective equipment and emergency procedures**

- The very fine particles can cause a fire or explosion, eliminate all ignition sources.

- Clean up spills immediately, observing precautions in protective equipment section.
- ELIMINATE all ignition sources.
- All equipment used when handling the product must be grounded.
- Stop leak if you can do it without risk.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- A vapor suppressing foam may be used to reduce vapors.
- Cover with plastic sheet to prevent spreading.
- Please note that materials and conditions to avoid.

#### **B. Environmental precautions :**

- Prevent entry into waterways, sewers, basements or confined areas.

#### **C. Methods and materials for containment and cleaning up**

- Dike and collect water used to fight fire.
- Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.
- Absorb the liquid and scrub the contaminated area with detergent and water.
- Large Spill; Dike far ahead of liquid spill for later disposal.
- Use clean non-sparking tools to collect absorbed material.

---

## **7. HANDLING AND STORAGE**

---

#### **A. Precautions for safe handling**

- Do not handle until all safety precautions have been read and understood.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use non-sparking tools.
- Take action to prevent static discharges.
- Wash thoroughly after handling.
- Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.
- Follow all MSDS/label precautions even after container is emptied because they may retain product residues.
- Use care in handling/storage.
- Loosen closure cautiously before opening.
- Avoid breathing vapors from heated material.
- Do not enter storage area unless adequately ventilated.
- All equipment used when handling the product must be grounded.
- Please note that materials and conditions to avoid.
- Be careful to heat.

- You need measurement of air concentration and ventilation in low, closed and confined areas due to lack of oxygen.

#### **B. Conditions for safe storage, including any incompatibilities**

- Keep away from heat, sparks, flames and high temperature – No smoking.
- Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Empty drums should be drained completely and properly blocked and immediately returned to a drum control or placed properly.

---

## **SECTION 8: Exposure controls/personal protection**

---

#### **A. Control parameters**

##### **Korea regulation**

Ethyl alcohol            TWA=1,000 ppm

##### **ACGIH regulation**

Ethyl alcohol            STEL=1,000 ppm

##### **Biological exposure index**

Ethyl alcohol            Not available

#### **B. Appropriate engineering controls**

- Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.  
Facilities for storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

#### **C. Individual protection measures, such as personal protective equipment.(PPE)**

##### **Respiratory protection**

- If exposure concentration of the material exceeds the permitted exposure standards, Wear NIOSH or European Standard EN 149 approved full or half face piece (with goggles) respiratory protective equipment.

##### **Eye protection**

- Wear appropriate protective glasses by considering physical and chemical properties of chemicals.

##### **Hand protection**

- Wear appropriate protective gloves by considering physical and chemical properties of chemicals.

##### **Body protection**

- Wear appropriate protective clothing by considering physical and chemical properties of chemicals.

---

## SECTION 9: Physical and chemical properties and safety characteristics

---

### A. Appearance

**Physical state** : liquid

**Colour** : Colorless

**B. Odour** : Wine or whiskey smell

**C. Odor threshold** : 10ppm

**D. Melting point/freezing point** : -114.1°C

**E. Boiling point or initial boiling point and boiling range** : 78.5°C

**F. Flash point** : 13°C(C.C)

**G. Lower and upper explosion limit/ flammability limit** : 3.1 / 27.7 %

**H. Flammability** : Not applicable

**I. Auto-ignition temperature** : 400°C

**J. Decomposition temperature** : Not available

**K. pH** : 7 (10g/L, H<sub>2</sub>O, 20°C)

**L. Kinematic viscosity** : 1.074 cP (20°C, mPa s) (viscosity)

**M. Solubility** : 789,000 mg/l (20°C)

**N. Partition coefficient n-octanol/water (log value)** : -0.32 (Log Kow)

**O. Vapour pressure** : 5.8 kPa (20°C)

**P. Density and/or relative density** : 0.79679 (15°C/15°C)

**Q. Relative vapour density** : 1.6 (air=1)

**R. Particle characteristics** : Not available

**S. Evaporation rate** : Not available

**T. Molecular weight** : 46.07

---

## SECTION 10: Stability and reactivity

---

### A. Reactivity

- Highly flammable liquid and vapour
- May violently polymerize and result in fire and explosion.
- May form explosive mixtures at the flashpoint or above.
- Can decompose at high temperatures forming toxic gases.
- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- May cause vapor explosion and poison hazard indoors, outdoors or in sewers.
- Some of the liquid may release vapors causing dizziness and suffocation.
- Spilled material may cause fire or explosion hazard

- Vapors may form explosive mixtures with air.

#### **B. Chemical stability**

- Some of these materials may burn, but none ignite readily.

#### **C. Possibility of hazardous reactions**

- Highly flammable liquid and vapour
- May violently polymerize and result in fire and explosion.
- May form explosive mixtures at the flashpoint or above.
- Can decompose at high temperatures forming toxic gases.
- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- May cause vapor explosion and poison hazard indoors, outdoors or in sewers.
- Spilled material may cause fire or explosion hazard
- Vapors may form explosive mixtures with air.

#### **D. Conditions to avoid**

- Keep away from heat, sparks, flames and high temperature – No smoking

#### **E. Incompatible materials**

- combustibles, reducing agents

#### **F. Hazardous decomposition products**

- Material may produce irritating and highly toxic gases by pyrolysis and combustion during burning
- Corrosive and/or toxic gases

---

## **SECTION 11: Toxicological information**

---

#### **A. Information on likely routes of exposure**

- Causes serious eye irritation

#### **B. Acute toxicity**

##### **Oral**

Ethyl alcohol                      Rat\_LD50 = 10,470 mg/kg bw (OECD Guideline 401)

##### **Dermal**

Ethyl alcohol                      Rabbit\_LDL0(lowest lethal concentration) = 20,000 mg/kg

##### **Inhalation**

Ethyl alcohol                      Rat(male)\_LC50=116.9 mg/L/ 4 hr/ vapour (equivalent or similar to OECD Guideline 403)

Rat(female)\_LC50=133.8 mg/L/ 4 hr/ vapour (equivalent or similar to OECD Guideline 403)

#### **C. Skin corrosion/irritation**



Ethyl alcohol No irritating as a result of skin irritation test using rabbit. (OECD Guideline 404, GLP)

#### D. Serious eye damage/irritation

Ethyl alcohol Eye irritation tests using rabbit showed conjunctival redness (Grade 1) in two out of three, but full reversal of all symptoms in animals occurred within 14 days (OECD Guideline 405)

#### E. Respiratory or skin sensitization

##### Respiratory sensitization

Ethyl alcohol In human, A vapor concentration of 5000 ppm was noted as irritating and uncomfortable to breathe, but tolerable. (Lester, 1951). A much higher concentration will cause tears and cough.

##### Skin sensitization

Ethyl alcohol No significant symptoms were observed as a result of skin sensitization tests using mouse (equivalent or similar to OECD Guideline 429)

#### F. Germ cell mutagenicity

Ethyl alcohol in vivo - No significant symptoms were observed as a result of the rodent dominant leisure assay test using a mouse(male). (equivalent or similar to OECD Guideline 478)  
in vitro - Negative results of Bacterial Reverse Automation Assay test using S. typhimurium TA1535, TA97, TA98, TA100, TA104 (equivalent or similar to OECD Guideline 471)

#### G. Carcinogenicity

Ethyl alcohol  
- KOSHA 1A(Limited to alcohol drinking)  
- IARC 1(Limited to alcohol drinking)  
- ACGIH A3  
- NTP Not applicable  
- OSHA TLV-A3  
- EU CLP Not applicable

#### H. Reproductive toxicity

Ethyl alcohol Two-Generation reproductive toxicity tests with mouse showed significant weight loss of male epididymitis and seminal vesicles in the group of 20.7 g/kg/day of F1, but Ethanol is not considered as reproductive toxicity because it was reversible by diet control.  
(OECD Guideline 416, NTP Protocol. Fertility assessment by continuous breeding)

#### I. STOT-single exposure

Ethyl alcohol

As a result of oral test using rat moderate decrease in activity and respiratory rate at 8,200 mg/kg, moderate paleness, grip and ataxia, moderate decrease in activity and respiratory rate at 9,840 mg/kg, moderate pupil response, moderate gripping and ataxia at 11,480 mg/kg, extreme decreases in activity and respiratory rate, moderate pupil response, moderate minor gripping and ataxia, and at 16070 mg/kg, moderate decrease in activity and respiratory rate, moderate pupil response slight paleness, abdominal tension and ataxia occurred.

As a result of inhalation test using rat moist and congested eyes, nasal discharge, eyelid closure, intermittent breathing, pain reflexes, anesthesia effect, and bent posture were found at the 4 high dose of group (155.0, 115.4, 93.4, 79.1 mg/l). As gross pathological findings relevance, acute dilation and congestion of the heart and moderate partial acute flatulence were observed in the lungs. Also, the lungs had a partial rash, infarction, and finally full of blood and swelling.

#### J. STOT-repeated exposure

Ethyl alcohol

No significant symptoms were observed as a result of repeated oral toxicity tests for 14 weeks using rat, NOAEL = 1,730 mg/kg bw (equivalent or similar to OECD Guideline 408, GLP)

Results of repeated 6-week inhalation toxicity tests using rat showed a significantly decrease in testosterone at a concentration of 2,000 ppm. (Read-Across (methanol:200-659-6))

#### K. Aspiration hazard

Ethyl alcohol

Not available

---

## 12. ECOLOGICAL INFORMATION

---

### A. Toxicity

#### Fish

Ethyl alcohol

96hr\_LC50(Pimephales promelas) = 15.3 g/L (US EPA method E03-05)

120hr\_NOEC (Danio rerio) = 250m g/L (equivalent or similar to OECD Guideline 212)

#### Crustaceans

Ethyl alcohol

48hr\_LC50(Ceriodaphnia dubia) = 5,012 mg/L (ASTM E729-80)

10d\_NOEC(Ceriodaphnia dubia) = 9.6 mg/L(reproduction)

#### Algae

Ethyl alcohol

3d\_EC50(Chlorella vulgaris) = 275mg/L (equivalent or similar to OECD

Guideline 201)

4d\_EC50(*Chlorella vulgaris*) = 675mg/L (equivalent or similar to OECD Guideline 201)

## B. Persistence and degradability

### Persistence

Ethyl alcohol -0.32 (Log Kow)

### Degradability

Ethyl alcohol 15d\_BOD=95%

## C. Bioaccumulative potential

### Bioaccumulation

Ethyl alcohol As a result of exposure test of *Cyprinus carpio* at 72 hour, the value of BCF is 1 in blood and tissues (gills, muscle, liver, kidney, intestine) (Read-Across cas no. 67-56-1)

### Biodegradation

Ethyl alcohol Not available

## D. Mobility in soil

Ethyl alcohol Log koc=0.2((Q)SAR)

## E. Other adverse effects

- Not available

---

## SECTION 13: Disposal considerations

---

### A. Disposal methods

- Waste must be disposed of in accordance with federal, state and local environmental control regulations.

### B. Disposal considerations

- Waste must be disposed of in accordance with federal, state and local environmental control regulations.

---

## SECTION 14: Transport information

---

A. UN number : 1170

B. UN Proper shipping name : ETHANOL(ETHYL ALCOHOL) or ETHANOL SOLUTION(ETHYL ALCOHOL SOLUTION)

C. Transport hazard class(es) : 3

- D. **Packing group, if applicable** : II
- E. **Environmental hazards** : Not applicable
- F. **Special precautions for user**
  - In case of fire : F-E
  - In case of leakage : S-D
- G. **Transport in bulk according to IMO instruments** : Not applicable

---

## 15. REGULATORY INFORMATION

---

### A. Regulation Information

<b>U.S.A management information (OSHA Regulation)</b>	Not applicable
<b>U.S.A management information (CERCLA Regulation)</b>	Not applicable
<b>U.S.A management information (EPCRA 302 Regulation)</b>	Not applicable
<b>U.S.A management information (EPCRA 304 Regulation)</b>	Not applicable
<b>U.S.A management information (EPCRA 313 Regulation)</b>	Not applicable
<b>Substance of Rotterdam Convention</b>	Not applicable
<b>Substance of Stockholm Convention</b>	Not applicable
<b>Substance of Montreal Protocol</b>	Not applicable
<b>EU classification (classification)</b>	
Ethyl alcohol	Flammable liquids Category 2
<b>EU classification (risk phrases)</b>	Not applicable
<b>EU SVHC list</b>	Not applicable
<b>EU Authorisation List</b>	Not applicable
<b>EU Restriction list</b>	Not applicable

### B. KOREA Regulatory information

<b>Occupational Safety and Health Act</b>	
Ethyl alcohol	Control parameters inventory substance
<b>Chemicals Control Act</b>	Not applicable
<b>Safety Control of Dangerous Substances Act</b>	
Ethyl alcohol	4 <sup>th</sup> class (Flammable liquid) Alcohol substances (Designated quantity 400L)
<b>Wastes Control Act</b>	

The waste which is produced in the facility is designated wastes and industrial wastes under Wastes Control Act Enforcement Ordinance [Annex1]

### C. Other regulation

**Persistent Organic Pollutants Act** Not applicable

---

## SECTION 16: Other information

---

### A. Information sources and references

- Korean SDS of Denatured Anhydrous Ethanol by Korea Alcohol Industrial Co., LTD.
- ACGIH; <https://www.acgih.org/>
- IARC; [http://monographs.iarc.fr/ENG/Classification/latest\\_classif.php](http://monographs.iarc.fr/ENG/Classification/latest_classif.php)
- NTP; <http://ntp.niehs.nih.gov/index.cfm>
- OSHA; <https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.119App>
- UN Recommendations on the Transport of Dangerous Goods-Model Regulations Twenty-first edition; [https://www.unece.org/trans/danger/publi/unrec/rev21/21files\\_e.html](https://www.unece.org/trans/danger/publi/unrec/rev21/21files_e.html)
- (KOMDI); <https://www.komdi.or.kr/ukiwi/biz/info/ukiwiBizInfoIMDGCodeList.do>
- Rules on the Occupational Safety and Health Act [Attached Table12]
- Enforcement rules of the Occupational Safety and Health Act [Attached Table21, 22, 23]
- Exposure criteria for chemicals and physical factors; Ministry of Employment and Labor (2020-48)
- Enforcement rules of the Occupational Safety and Health Act [Attached Table19]
- Enforcement decree of the Occupational Safety and Health Act [Attached Table13]
- substances under observation and restricted substances which are designated and announced[Attached Table2,]
- substances under observation and restricted substances which are designated and announced[Attached Table4]
- poisonous substances which are designated and announced [Attached Table] (Article 3 of the Enforcement Decree of the Hwapyeong Act and Article 2 of the Enforcement Decree of the Hwapyeong Act)
- Enforcement rules of the Chemicals Control Act [Attached Table10]
- WastesControlAct; <http://www.law.go.kr/LSW//lsInfoP.do?lsiSeq=212975&ancYd=20191231&ancNo=00843&efYd=20200701&nwJoYnInfo=N&efGubun=Y&chrClsCd=010202&ancYnChk=0#AJAX>
- (KFI); <http://hazmat.mpss.kfi.or.kr/material.do>
- Montreal Protocol ; <https://www.epa.gov/ozone-layer-protection/ozone-depleting-substances>
- Rotterdam Convention ; <http://www.pic.int/TheConvention/Chemicals/>

- Persistent Organic Pollutants Act; [Attached Table1]
- (OSHA); <https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.119AppA>
- (CERCLA, EPCRA 302, EPCRA 304, EPCRA 313); [https://www.epa.gov/sites/production/files/2015-03/documents/list\\_of\\_lists.pdf](https://www.epa.gov/sites/production/files/2015-03/documents/list_of_lists.pdf)
- EU SVHC list; <https://echa.europa.eu/authorisation-list>
- EU Authorisation List; <https://echa.europa.eu/substances-restricted-under-reach>
- EU Restriction list; [https://echa.europa.eu/information-on-chemicals/biocidal-active-substances?p\\_p\\_id=dissactivesubstances\\_WAR\\_dissactivesubstancesportlet&p\\_p\\_lifecycle=1&p\\_p\\_state=normal&p\\_p\\_mode=view&p\\_p\\_col\\_id=column-1&p\\_p\\_col\\_pos=2&p\\_p\\_col\\_count=3&dissactivesubstances\\_WAR\\_dissactivesubstancesportlet\\_javax.portlet.action=dissActiveSubstancesAction](https://echa.europa.eu/information-on-chemicals/biocidal-active-substances?p_p_id=dissactivesubstances_WAR_dissactivesubstancesportlet&p_p_lifecycle=1&p_p_state=normal&p_p_mode=view&p_p_col_id=column-1&p_p_col_pos=2&p_p_col_count=3&dissactivesubstances_WAR_dissactivesubstancesportlet_javax.portlet.action=dissActiveSubstancesAction)
- KOSHA Guidance; Development of Guidelines for Selection of Respirators for Workers Exposed to Chemical Substances
- NCIS; <http://ncis.nier.go.kr/>
- ECHA; <https://echa.europa.eu/information-on-chemicals/registered-substances>
- HSDB; <https://pubchem.ncbi.nlm.nih.gov/>
- Epa; <https://comptox.epa.gov/dashboard/>
- EU SVHC list : [https://echa.europa.eu/de/candidate-list-table?p\\_p\\_id=disslists\\_WAR\\_disslistsportlet&p\\_p\\_lifecycle=1&p\\_p\\_state=normal&p\\_p\\_mode=view&p\\_p\\_col\\_id=column1&p\\_p\\_col\\_pos=2&p\\_p\\_col\\_count=3&disslists\\_WAR\\_disslistsportlet\\_javax.portlet.action=searchDissLists](https://echa.europa.eu/de/candidate-list-table?p_p_id=disslists_WAR_disslistsportlet&p_p_lifecycle=1&p_p_state=normal&p_p_mode=view&p_p_col_id=column1&p_p_col_pos=2&p_p_col_count=3&disslists_WAR_disslistsportlet_javax.portlet.action=searchDissLists)

#### B. Issuing date

- Jan 03th 2022

#### C. Revision number and date

**Revision number** : **1**

**Date of the latest revision Others** : **June 30th 2023**

#### D. Others

- This SDS is prepared based on GHS classification in accordance with 29 CFR 1910.1200.
- The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose
- This SDS is written for assisting buyers, handlers or the third party to manage materials. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein. The recipient of our products is responsible for observing any laws and guidelines applicable.
- The content contained in this SDS may vary by country and region, and may not be consistent with

the content of the actual relevant regulations. Buyer and handlers are responsible for identifying and complying with the relevant government and local regulations