Safety Data Sheet

SECTION 1 : Identification

A. GHS Product Name: Ethanol B95

- B. Other means of identification : Not available
- C. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives, sealants, Anti-Freeze and de-icing products, Washing and cleaning products, Metal surface treatment products (Electroplating agents), (Flame retardants and Fire preventing agents), Fuels and additives, Feed materials, Intermediates, Laboratory chemicals, Solvent and extraction agents, Stabilizers, Viscosity adjusters, Cosmetics, personal care products, Perfumes, fragrances, Pharmaceuticals, Fertilizers, Air care products, Biocidal products, Others

Restriction on use : Use for recommended use only

D. Supplier's information

Company name : Korea Alcohol Industrial Co., LTD.
 Address : (Headquater) 14, Tapsil-ro 35beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do (Ulsan office) 66, Sanggae-ro, Nam-gu, Ulsan
 Telephone number : (Headquater)031-881-8100, (Ulsan office)052-259-4761~2
 Respondent : Not available

Fax : Not available

E. Emergency phone number

Opening hours : (Headquarter)031-881-8100, (Ulsan office)052-259-4761~2

Other comments (e.g. language(s) of the phone service) : www.ka.co.kr / Sales or HSE Department

SECTION 2 : Hazard identification

A. Classification of the substance or mixture

Flammable liquids : Category 2

Serious eye damage /eye irritation: Category 2

B. GHS label elements, including precautionary statements Pictogram and symbol :



페이지 1/16

Signal word : Danger

Hazard statements :

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

Precautionary statements

Precaution :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection

Response :

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use adequate to extinguish.

Storage :

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal :

P501 Dispose of contents/container to in accordance with federal, state and local environmental control regulations.

C. Other hazards which do not result in classification

Not available

SECTION 3: Composition/information on ingredients

Chemical Name	Common Name (Synonyms)	CAS No.	EC number	Content (%)
Ethyl alcohol	Ethanol	64-17-5	200-578-6	95.1≤
Water	Water	7732-18-5	231-791-2	<4.9
Acetaldehyde	Ethanal	75-07-0*	200-836-8	<0.1

Methyl alcohol	Methanol	67-56-1*	200-659-6	<0.1
Isopropyl alcohol	2-Propanol	67-63-0*	200-661-7	<0.1
n-Propyl alcohol	1-Propanol	71-23-8*	200-746-9	<0.1
n-Butyl alcohol	1-butanol	71-36-3*	200-751-6	<0.1
iso-Butyl alcohol	Isobutanol	78-83-1*	201-148-0	<0.1
iso-Amyl alcohol	3-Methyl-1-butanol	123-51-3*	204-633-5	<0.1
Active-Amyl alcohol	2-Methylbutan-1-ol	137-32-6*	205-289-9	<0.1
1,1-Ethyl Acetal	1,1-Diethoxyethane	105-57-7*	203-310-6	<0.1
Denatonium benzoate(Bitrex)	Benzyldiethyl[(2,6- xylylcarbamoyl)meth yl]ammonium benzoate	3734-33-6*	223-095-2	<0.1

SECTION 4: First-aid measures

A. Description of necessary first-aid measures

After eye contact	IF IN EYES: Rinse cautiously with water for several minutes. If possible, remove
	contact lenses. Keep washing
	If eye irritation persists: Get medical advice/attention.
After skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower].
	Call emergency medical service.
	Remove and isolate contaminated clothing and shoes.
	For minor skin contact, avoid spreading material on unaffected skin.
	In case of burns, immediately cool affected skin for as long as possible with
	cold water. Do not remove clothing if adhering to skin.
	Wash skin with soap and water.
After inhalation	IF exposed or concerned: Get medical advice/attention.
	Move victim to fresh air.
	Keep victim warm and quiet.
After ingestion	IF exposed or concerned: Get medical advice/attention.
B. Most important sympto	oms and effects, both acute and delayed

- Causes serious eye irritation
- C. Indication of immediate medical attention and notes for physician, if necessary
 - Ensure that medical personnel are aware of the material(s) involved and take precautions to protect

SECTION 5: Fire-fighting measures

A. Suitable extinguishing media

- Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
- Use dry sand or earth to smother fire.

B. Specific hazards arising from the chemical

- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- Spilled material may cause fire or explosion hazard
- May cause vapor explosion and poison hazard indoors, outdoors or in sewers.
- Some of these materials may burn, but none ignite readily.
- Vapors may form explosive mixtures with air.
- May violently polymerize and result in fire and explosion.
- Vapors may travel to a source of ignition and ignite.
- Material may produce irritating and highly toxic gases by pyrolysis and combustion during burning
- May form explosive mixtures at the flashpoint or above.
- Highly flammable liquid and vapour

C. Special protective actions for fire-fighters

- Rescuers should put on appropriate protective gear.
- Evacuate area and fight fire from a safe distance.
- Many liquids are lighter than water.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas
- Substance may be transported hot.
- Substance may be transported in a molten form.
- Dike fire-control water for later disposal; do not scatter the material.
- Move containers from fire area if you can do it without risk.
- In case of the tank fire, extinguish at maximum distance or use unmanned fire extinguishing equipment.
- In case of the tank fire, keep cooling down the tank with plenty of water after fire is extinguished.
- In case of tank fire, if there is a high sound level on the pressure relief device or if the tank is discolored, immediately withdraw it.
- In the case of a tank fire, withdraw from the tank engulfed in flames.
- In the case of a large-scale fire of a tank, use unmanned fire extinguishing equipment and, if not possible, leave it to burn.

SECTION 6: Accidental release measures

A. Personal precautions, protective equipment and emergency procedures

- The very fine particles can cause a fire or explosion, eliminate all ignition sources.
- Clean up spills immediately, observing precautions in protective equipment section.
- ELIMINATE all ignition sources.
- All equipment used when handling the product must be grounded.
- Stop leak if you can do it without risk.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- A vapor suppressing foam may be used to reduce vapors.
- Cover with plastic sheet to prevent spreading.
- Please note that materials and conditions to avoid.

B. Environmental precautions :

- Prevent entry into waterways, sewers, basements or confined areas.

C. Methods and materials for containment and cleaning up

- Dike and collect water used to fight fire.
- Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.
- Absorb the liquid and scrub the contaminated area with detergent and water.
- Large Spill; Dike far ahead of liquid spill for later disposal.
- Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Do not handle until all safety precautions have been read and understood.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use non-sparking tools.
- Take action to prevent static discharges.
- Wash thoroughly after handling.
- Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.
- Follow all MSDS/label precautions even after container is emptied because they may retain product residues.
- Use care in handling/storage.
- Loosen closure cautiously before opening.
- Avoid breathing vapors from heated material.
- Do not enter storage area unless adequately ventilated.

- All equipment used when handling the product must be grounded.
- Please note that materials and conditions to avoid.
- Be careful to heat.
- You need measurement of air concentration and ventilation in low, closed and confined areas due to lack of oxygen.
- B. Conditions for safe storage, including any incompatibilities
 - Keep away from heat, sparks, flames and high temperature No smoking.
 - Keep container tightly closed.
 - Store in a well-ventilated place. Keep cool.
 - Store locked up.
 - Empty drums should be drained completely and properly blocked and immediately returned to a drum control or placed properly.

SECTION 8: Exposure controls/personal protection

A. Control parameters

Korea regulation			
Ethyl alcohol	TWA = 1,000 ppm		
Water	Not applicable		
ACGIH regulation			
Ethyl alcohol	STEL = 1,000 ppm		
Water	Not applicable		
Biological exposure index			
Ethyl alcohol	Not applicable		
Water	Not applicable		

B. Appropriate engineering controls

- Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.
- Facilities for storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

C. Individual protection measures, such as personal protective equipment.(PPE) Respiratory protection

- If exposure concentration of the material exceeds the permitted exposure standards, Wear NIOSH or European Standard EN 149 approved full or half face piece (with goggles) respiratory protective equipment

Eye protection

- Wear appropriate protective goggles by considering physical and chemical properties of chemicals.

페이지 6/16

Hand protection

- Wear appropriate protective gloves by considering physical and chemical properties of chemicals.

Body protection

- Wear appropriate protective clothing by considering physical and chemical properties of chemicals.

SECTION 9: Physical and chemical properties and safety characteristics

- A. Appearance
 - Physical state : liquid
 - Colour : Colorless
- B. Odour : Wine or whiskey smell
- C. Odor threshold : 10 ppm
- **D.** Melting point/freezing point : -114.1°C
- E. Boiling point or initial boiling point and boiling range : 78.5℃
- F. Flash point : 13°C(C.C)
- G. Lower and upper explosion limit/ flammability limit : 3.1 / 27.7 %
- H. Flammability : Not applicable
- I. Auto-ignition temperature : 400°C
- J. Decomposition temperature : Not available
- **K. pH** : 7 (10g/L, H2O, 20°C)
- L. Kinematic viscosity : 1.074 cP (20°C, mPa s) (viscosity)
- M. Solubility: 789,000 mg/l (20°C)
- N. Partition coefficient n-octanol/water (log value) : -0.32 (Log Kow)
- **O.** Vapour pressure : 5.8 kPa (20°C)
- **P.** Density and/or relative density : 0.81601 (15°C/15°C)
- Q. Relative vapour density : 1.6 (air=1)
- R. Particle characteristics : Not available
- S. Evaporation rate : Not available
- T. Molecular weight: 46.07

SECTION 10: Stability and reactivity

A. Reactivity

- Highly flammable liquid and vapour
- May violently polymerize and result in fire and explosion.
- May form explosive mixtures at the flashpoint or above.

- Can decompose at high temperatures forming toxic gases.
- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- May cause vapor explosion and poison hazard indoors, outdoors or in sewers.
- Some of the liquid may release vapors causing dizziness and suffocation.
- Spilled material may cause fire or explosion hazard
- Some of these materials may burn, but none ignite readily.

B. Chemical stability

- Some of these materials may burn, but none ignite readily.

C. Possibility of hazardous reactions

- Highly flammable liquid and vapour
- May violently polymerize and result in fire and explosion.
- May form explosive mixtures at the flashpoint or above.
- Can decompose at high temperatures forming toxic gases.
- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- May cause vapor explosion and poison hazard indoors, outdoors or in sewers.
- Some of the liquid may release vapors causing dizziness and suffocation.
- Spilled material may cause fire or explosion hazard

D. Conditions to avoid

- Keep away from heat, sparks, flames and high temperature – No smoking

E. Incompatible materials

- combustibles, reducing agents

F. Hazardous decomposition products

- Material may produce irritating and highly toxic gases by pyrolysis and combustion during burning
- Corrosive and/or toxic gases

SECTION 11: Toxicological information

A. Information on likely routes of exposure

- Causes serious eye irritation
- B. Acute toxicity

Oral

```
Ethyl alcohol
Water
```

 $Rat_LD50 = 10,470 mg/kg bw (OECD Guideline 401)$ $Rat_LD50 > 90,000 mg/kg$

Dermal

Ethyl alcohol	Rabbit_LDL0(lowest lethal concentration) = 20,000 mg/kg	
Water	Not available	
Inhalation		
Ethyl alcohol	Rat(male)_LC50=116.9 mg/L/ 4 hr/ vapour (equivalent or similar to OECD Guideline 403) Rat(female)_LC50=133.8 mg/L/ 4 hr/ vapour (equivalent or similar to OECD Guideline 403)	
Water	Not available	
C. Skin corrosion/irritation		
Ethyl alcohol	No irritating as a result of skin irritation test using rabbit. (OECD Guideline 404, GLP)	
Water	Not available	
D. Serious eye damage/irritati		
Ethyl alcohol	Eye irritation tests using rabbit showed conjunctival redness (Grade 1) in two out of three, but Full reversal of all symptoms in animals occurred within 14 days (OECD Guideline 405)	
Water	Not available	
E. Respiratory or skin sensitiza	ntion	
Respiratory sensitization		
Ethyl alcohol	In human, A vapor concentration of 5000 ppm was noted as irritating and uncomfortable to breathe, but tolerable. (Lester, 1951). A much higher concentration will cause tears and cough.	
Water	Not available	
Skin sensitization		
Ethyl alcohol	No significant symptoms were observed as a result of skin sensitization tests using mouse (equivalent or similar to OECD Guideline 429)	
Water	Not available	
F. Germ cell mutagenicity		
Ethyl alcohol	in vivo - No significant symptoms were observed as a result of the rodent dominant leisure assay test using a mouse. (male). (equivalent or similar to OECD Guideline 478) in vitro - Negative results of Bacterial Reverse Automation Assay test using S. typimurium TA1535, TA97, TA98, TA100, TA104 (equivalent or similar to OECD Guideline 471)	
Water	Not available	
G. Carcinogenicity		
Ethyl alcohol		

페이지 9/16

- KOSHA	1A(Limited to alcohol drinking)
- IARC	1(Limited to alcohol drinking)
- ACGIH	A3
- NTP	Not applicable
- OSHA	TLV-A3
- EU CLP	Not applicable
Water	Not applicable
- KOSHA	Not applicable
- IARC	Not applicable
- ACGIH	Not applicable
- NTP	Not applicable
- OSHA	Not applicable
- EU CLP	Not applicable

H. Reproductive toxicity

Ethyl alcohol

two-Generation reproductive toxicity tests with mouse showed significant weight loss of male epididymides and seminal vesicles in the group of 20.7 g/kg/day of F1, but Ethanol is not considered as reproductive toxicity because it was reversible by diet control.

(OECD Guideline 416, NTP Protocol. Fertility assessment by continuous breeding)

Not available

I. STOT-single exposure

Water

Ethyl alcohol

As a result of oral test using rat moderate decrease in activity and respiratory rate at 8,200 mg/kg, moderate paleness, grip and ataxia, moderate decrease in activity and respiratory rate at 9,840 mg/kg, moderate pupil response, moderate gripping and ataxia at 11,480 mg/kg, extreme decreases in activity and respiratory rate, moderate pupil response, moderate minor gripping and ataxia, and at 16070 mg/kg, moderate decrease in activity and respiratory rate, moderate pupil response, moderate minor gripping and ataxia, and at 16070 mg/kg, moderate decrease in activity and respiratory rate, moderate pupil response slight paleness, abdominal tension and ataxia occurred.

As a result of inhalation test using rat moist and congested eyes, nasal discharge, eyelid closure, intermittent breathing, pain reflexes, anesthesia effect, and bent posture were found at the 4 high dose of group (155.0, 115.4, 93.4, 79.1 mg/l). As gross pathological findings relevance, acute dilation and congestion of the heart and moderate partial acute flatulence were observed in the lungs. Also, the lungs had a partial rash, infarction, and finally full of blood and swelling.

페이지 10 / 16

Water	Not available
J. STOT-repeated exposure	
Ethyl alcohol	No significant symptoms were observed as a result of repeated oral toxicity tests for 14 weeks using rat, NOAEL = 1,730 mg/kg bw (equivalent or similar to OECD Guideline 408, GLP) Results of repeated 6-week inhalation toxicity tests using rat showed a significantly decrease in testosterone at a concentration of 2,000 ppm. (Read-Across (methanol:200-659-6))
Water	Not available
K. Aspiration hazard	
Ethyl alcohol	Not available
Water	Not available

12. ECOLOGICAL INFORMATION

A. Toxicity

	-	
	Fish	
	Ethyl alcohol	96hr_LC50(Pimephales promelas) = 15.3 g/L (US EPA method E03-05)
		120hr_NOEC (Danio rerio) = 250m g/L (equivalent or similar to OECD
		Guideline 212)
	Water	Not available
	Crustaceans	
	Ethyl alcohol	48hr_LC50(Ceriodaphnia dubia) = 5,012 mg/L (ASTM E729-80)
		10d_NOEC(Ceriodaphnia dubia) = 9.6 mg/L(reproduction)
	Water	Not available
	Algae	
	Ethyl alcohol	3d_EC50(Chlorella vulgaris) = 275mg/L (equivalent or similar to OECD
		Guideline 201)
		4d_EC50(Chlorella vulgaris) = 675mg/L (equivalent or similar to OECD
		Guideline 201)
	Water	Not available
В.	Persistence and degradabili	ty
	Persistence	
	Ethyl alcohol	-0.32 (Log Kow)
	Water	Not available
	Degradability	

페이지 11 / 16

	Ethyl alcohol	15d_BOD=95%
	Water	Not available
С.	Bioaccumulative potential	
	Bioaccumulation	
	Ethyl alcohol	As a result of exposure test of Cyprinus carpio at 72 hour, the value of BCF
		is 1 in blood and tissues (gills, muscle, liver, kidney, intestine) (Read-Across
		cas no. 67-56-1)
	Water	Not available
	Biodegradation	
		Not available
D.	Mobility in soil	
	Ethyl alcohol	Log koc=0.2 ((Q)SAR)
	Water	Not available
Ε.	Other adverse effects	
	- Not available	

SECTION 13: Disposal considerations

A. Disposal methods

- Waste must be disposed of in accordance with federal, state and local environmental control regulations.
- B. Disposal considerations
 - Waste must be disposed of in accordance with federal, state and local environmental control regulations.

SECTION 14: Transport information

- **A. UN number :** 1170
- **B. UN Proper shipping name** : ETHANOL(ETHYL ALCOHOL) or ETHANOL SOLUTION(ETHYL ALCOHOL SOLUTION)
- C. Transport hazard class(es) : 3
- D. Packing group, if applicable : II
- E. Environmental hazards : Not applicable
- F. Special precautions for user

In case of fire : F-E

페이지 12 / 16

In case of leakage : S-D

G. Transport in bulk according to IMO instruments : Not applicable

15. REGULATORY INFORMATION A. Regulation Information **U.S.A management information** Not applicable (OSHA Regulation) **U.S.A management information** Not applicable (CERCLA Regulation) **U.S.A management information** Not applicable (EPCRA 302 Regulation) **U.S.A management information** Not applicable (EPCRA 304 Regulation) **U.S.A management information** Not applicable (EPCRA 313 Regulation) Substance of Rotterdam Convention Not applicable Substance of Stockholm Convention Not applicable Substance of Montreal Protocol Not applicable EU classification (classification) Flammable liquids Category 2 EU classification (risk phrases) Not applicable **EU SVHC list** Not applicable **EU** Authorisation List Not applicable **EU Restriction list** Not applicable B. KOREA Regulatory information **Occupational Safety and Health Act** Ethyl alcohol Control parameters inventory substance Water Not applicable **Chemicals Control Act** Not applicable Safety Control of Dangerous Substances Act Ethyl alcohol 4th class (Flammable liquid) Alcohol substances (Designated quantity 400 L) Water Not applicable Wastes Control Act The waste which is produced in the facility is designated wastes and industrial wastes under Wastes Control Act Enforcement Ordinance [Annex1] C. Other regulation

페이지 13 / 16

SECTION 16: Other information

A. Information sources and references

- Korean SDS of Ethanol W provided by Korea Alcohol Industrial Co., LTD.
- ACGIH; https://www.acgih.org/
- IARC; http://monographs.iarc.fr/ENG/Classification/latest_classif.php
- NTP; http://ntp.niehs.nih.gov/index.cfm
- OSHA; https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.119App
- UN Recommendations on the Transport of Dangerous Goods-Model
- Regulations Twenty-firstedition; https://www.unece.org/trans
- /danger/publi/ unrec/rev21/21files_e.html
- (KOMDI); https://www.komdi.or.kr/ukiwi/biz/info/ukiwiBizInfoIMDGCodeList.do
- Rules on the Occupational Safety and Health Act [Attached Table12]
- Enforcement rules of the Occupational Safety and Health Act [Attached Table21, 22, 23]
- Exposure criteria for chemicals and physical factors; Ministry of Employment and Labor (2020-48)
- Enforcement rules of the Occupational Safety and Health Act [Attached Table19]
- Enforcement decree of the Occupational Safety and Health Act [Attached Table13]
- substances under observation and restricted substances which are designated and announced[Attached Table2,]
- substances under observation and restricted substances which are designated and announced[Attached Table4]
- poisonous substances which are designated and announced [Attached Table]
 (Article 3 of the Enforcement Decree of the Hwapyeong Act and Article 2 of the Enforcement Decree of the Hwapyeong Act)
- Enforcement rules of the Chemicals Control Act [Attached Table10]
- WastesControlAct; <u>http://www.law.go.kr/LSW//lsInfoP.do?lsiSeq=212975&ancYd</u>= 20191231&ancNo=00843&efYd= 20200701&nwJoYnInfo=N&efGubun=Y&chrClsCd= 010202&ancYnChk=0#AJAX
- (KFI); http://hazmat.mpss.kfi.or.kr/material.do
- Montreal Protocol ; https://www.epa.gov/ozone-layer-protection/ozone-depleting-substances
- Rotterdam Convention ; http://www.pic.int/TheConvention/Chemicals/
- Persistent Organic Pollutants Act; [Attached Table1]
- (OSHA); https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.119AppA
- (CERCLA, EPCRA 302, EPCRA 304, EPCRA 313); https://www.epa.gov/sites/production/files/2015-

페이지 14 / 16

03/documents/list_of_lists.pdf

- EU SVHC list; https://echa.europa.eu/authorisation-list
- EU Authorisation List; https://echa.europa.eu/substances-restricted-under-reach
- EU Restriction list; <u>https://echa.europa.eu/information-on-chemicals/biocidal-active</u> substances?p_p_id= dissactivesubstances_WAR_dissactivesubstancesportlet&p_p_lifecycle=1&p _p_state=normal&p_p_mode=view&p_p_col_id=column-1&p_p_col_pos=2&p_p_col_count=3&_ dissactivesubstances_WAR_dissactivesubstancesportlet_javax.portlet.action=dissActive Substances Action
- KOSHA Guidance; Development of Guidelines for Selection of Respirators for Workers Exposed to Chemical Substances
- NCIS; http://ncis.nier.go.kr/
- ECHA; https://echa.europa.eu/information-on-chemicals/registered-substances
- HSDB; https://pubchem.ncbi.nlm.nih.gov/
- Epa; https://comptox.epa.gov/dashboard/
- EU SVHC list : https://echa.europa.eu/de/candidate-list table?p_p_id=disslists_WAR_disslistsportlet&p_p_lifecycle=1&p_p_state=normal&p_p_mode =view&p_p_col_id=column-
 - 1&p_p_col_pos=2&p_p_col_count=3&_disslists_WAR_disslistsportlet_javax.portlet.action=
- searchDissLists

B. Issuing date

- Jul 17th 2023
- C. Revision number and date

Revision number : 0

Date of the latest revision Others : Not applicable

D. Others

- This SDS is prepared based on GHS classification in accordance with 29 CFR 1910.1200.
- The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose
- This SDS is written for assisting buyers, handlers or the third party to manage materials. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein. The recipient of our products is responsible for observing any laws and guidelines applicable.
- The content contained in this SDS may vary by country and region, and may not be consistent with the content of the actual relevant regulations. Buyer and handlers are responsible for identifying and complying with the relevant government and local regulations

페이지 15 / 16

페이지 16 / 16